

PFAFF

fine sewing

3371-10/01 Electronic lockstitch button sewer

Flexibility:

- Direct selection of 30 standard stitch patterns (= set programs)
- 10-200% alteration of the seam pattern in the X and Y direction (in 1% steps)
- Memory for 99 different seam diagrams
- Buttons from 8 to 30 mm diameter can be sewn
- Buttons can be attached with or without stem
- For 2 hole, 3 hole and 4 hole buttons







Performance/Quality:







- Neat, harmonious seam pattern
- Short, cut thread ends
- High productivity due to short cycle times and sewing speeds up to 2,500 spm
- Electromagnetically controlled functions - No compressed air required
- Easy to service owing to the central fresh oil lubrication system

Operation:

- Fast and easy programming of new stitch patterns on the new graphic control panel S2
- Direct access to 8 preferred stitch patterns
- Quick and easy storage of 3- bartack-sequences (cycles) with up to 16 stitch patterns
- Easily understandable operator panel with large display



Sewing area	Sewing speed (s.p.m)	Stitch length	Hook	Presser foot lift	Thread trimmer
					
max. 6.5 x 6.5 mm	max. 2,500	0.1 - 6.5 mm	CB Hook	max. 13 mm	●

Wiper	Bobbin capacity counter	Clamp feed	Needle system	Stitch type	Motor
					
●	●	●	DPx17 (135x17)	Lockstitch	375 W



- Direct access to preferred sewing programs with the use of the operator panel keys 1-8
- Simple alteration of seam program parameters, and of program number, speed, x-y factors
- Pre-selectable sequence programs (C1, C2, C3) with up to 16 program items
- Easy access to parameters for adjustment and service functions

Specifications:

Feed stroke: intermittent

Needle bar stroke: 46 mm

Data memory: Flash/CMOS RAM

Seam patterns: 1-99 sewing programs

Bobbin thread monitoring:

With piece counter (max. 9999 sewing cycles)

Data protection:

After power failures, the selected sewing program remains active

Dimensions: Length: 1,060 mm, width: 600 mm, height: 840 mm (standard stand)

Weight: Sewing head 42 kilos, control box 3 kilos

Input power rating: 1.2 kW (220V)